



HENKEL Australia Pty Ltd  
A.C.N. 001 302 996

135-141 Canterbury Road  
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200  
Fax: (03) 9728 5877  
Customer Service 1300 736 777

Distributed by  
Solvents Australia Pty Ltd  
ABN 74 003 523 117  
77 Bassett Street  
Mona Vale NSW 2100  
PO Box 928  
Mona Vale NSW 1660

Tel: (02)9979 6866  
Fax: (02)9979 6864

---

## Technical Data Bulletin

---

### TURCO 6776 L.O.

MATERIAL NO. 379231

### ENVIRONMENTALLY ADVANTAGED PAINT REMOVER

#### DESCRIPTION

TURCO 6776 L.O. is a thixotropic, light green liquid remover developed for stripping resistant finishes such as epoxies, epoxy primers, polyurethanes, alkyds and similar catalysed paints.

TURCO 6776 L.O. paint remover offers a significant advance in improving work place safety since it does not generate obnoxious fumes or odours and is free from methylene chloride, chlorinated solvents, phenols, chromates, ammonia and amines.

The product can be used on aluminium, mild steel, cast iron, and titanium when used as directed. TURCO 6776 L.O. is not recommended for use on high strength steel and magnesium. TURCO 6776 L.O. meets the "effects on metals" requirements of MIL-R-81903 A.

#### BENEFITS:

TURCO 6776 L.O. offers these features:

1. Safer to personnel.
2. Significantly lower waste disposal costs.
3. Can be easily treated on site (see MSDS).
4. Amount of stripper used is quite often less than conventional methylene chloride strippers.
5. No flash point to boil (Pensky Martens)
6. Used as received. No mixing or dilution required
7. Clings to vertical and overhead surfaces
8. Free from obnoxious fumes and odours
9. Positive pressure air respirators not required.

#### USE INSTRUCTIONS

Application: Apply a thick, uniform coating to surface being stripped by means of non-atomising spray or brushing. Allow sufficient time for stripper to work. Performance improves as temperature increases. Agitation with a stiff bristle brush after dwell time is completed will aid removal of the finish.

Removal: Squeegee off bulk of stripped paint with TURCO 6776 L.O., followed by high pressure water rinse.

## **DISPOSAL INFORMATION**

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to your HENKEL AUSTRALIA MATERIAL SAFETY DATA SHEET for additional disposal information.

Concentrate: (1) Transfer to reclaiming centre for recycling or reuse, if possible. (2) Transfer to licensed hazardous waste treatment or disposal site for disposition under applicable local, state and regional regulations as hazardous waste. (3) Small amounts may be dissolved in water and treated as described below. The clarified water may be released to sewer if local regulations permit.

Spend solution and rinses: Dispose per (1) or (2) above, or heavy metals (if present) may be precipitated by pH adjustment to 9.5 - 10.5; the pH of the separated water should then be readjusted to pH 7.0 - 8.0. The clarified water may be released to sewer if local regulations permit.

## **CAUTION:**

TURCO 6776 L.O. contains formic acid. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in confined areas. Avoid prolonged breathing of vapours. Use with adequate (equivalent to outdoors) ventilation.

Protective clothing, such as chemical face shield or goggles and gloves should be worn and an approved respirator equipped with a mechanical filter should be worn for mist conditions.

Store containers at a temperature below 40°C.

Before using this product refer to container label and HENKEL AUSTRALIA MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

## **NOTICE:**

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

*FEBRUARY 2003*

® Registered Tradename HENKEL Australia Pty Ltd  
® Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: [admin@solvents.net.au](mailto:admin@solvents.net.au)