



HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO DESEALZIT 1

Material No. 378372

DESCRIPTION:

TURCO DESEALZIT 1 is a heavy duty viscous paint stripping compound formulated primarily for the removal of rubberised paints or sealants and vinyl tile adhesive residues.

TURCO DESEALZIT 1 will remove lacquers and varnishes from wood surfaces without the danger of staining or raising the grain of the timber. It will also strip a wide variety of paint coatings or graffiti from stone, brick, concrete and metal surfaces.

BENEFITS:

TURCO DESEALZIT 1 offers these benefits:

1. Non-flammable.
2. Clings well to vertical surfaces.
3. Can be applied by either brush or spray.
4. Readily rinses from surfaces with cold water.
5. Very slow drying enabling it to penetrate multiple paint layers for effective removal.

HOW TO USE TURCO DESEALZIT 1:

Apply by brush, swab or direct displacement pump. Do not atomise. Allow sufficient time to work, 10-45 minutes, depending upon prevailing weather conditions. Do not allow the product to dry out on the surface. Remove residues with water hose or high pressure cleaner. A putty knife or paint scraper can also be used.

Coverage - 1 litre per square metre.

Note: TURCO DESEALZIT 1 is not recommended for use on materials such as plastics, rubbers or any metals, which can be affected by chlorinated hydrocarbons.

DISPOSAL INFORMATION:

Dispose of spent remover and paint residues per local regulations.

CAUTION:

TURCO DESEALZIT 1 contains chlorinated hydrocarbons and an organic acid. Do not spray in closed or confined areas. Use only with adequate (equivalent to outdoor) ventilation. Avoid breathing of vapour for prolonged periods. Avoid contact with eyes, skin or clothing. Do not take internally. Protective solvent and acid resistant clothing should be worn when handling this product, ie: industrial gloves, overalls, proper goggles or face mask. Use care when opening containers to avoid spurting, ie. open lid of container slowly in hot weather. Do not store in direct sunlight or in damp areas.

Refer to the HENKEL MATERIAL SAFETY DATA SHEET for additional handling, precautionary and first aid information.

June 2002

® Registered Tradename HENKEL Australia Pty Ltd
® Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au