

FOAM BLANKET 605

FOAM BLANKET ADDITIVE

1. DESCRIPTION

FOAM BLANKET 605 is a specially formulated product to control fumes in caustic etching and acidic anodising tanks. When using as recommended, it forms a thick layer of foam which suppresses fumes.

2. PROPERTIES

FOAM BLANKET 605 is a brown liquid which is soluble in water, caustic and acidic solutions.

FOAM BLANKET 605 has a neutral pH. It is neither flammable nor corrosive. Prolonged skin contact may cause slight irritation – if skin contact occurs, wash off with water.

3. METHOD OF OPERATION

Use about 50 mL of **FOAM BLANKET 605** in a tank of surface area 10 sqm. Wait for a while to allow foam formation. If sufficient foam is not formed, then add **FOAM BLANKET 605** in increments of 10 mls until the desired level is achieved. Do not add more product than required, otherwise excessive foam will be formed.

3. PACKAGING

FOAM BLANKET 605 is packed in 25 litre containers.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.