



Technologies

TECHNICAL INFORMATION RIDSOLVE 300W GUNWASH

1. TYPE

Medium evaporation rate paint line solvent.

2. DESCRIPTION

Blend of alcohol, amines and glycol ethers exhibiting powerful solvent action combined with an intermediate evaporation rate, for the flushing of water based automotive paint lines and spray guns.

3. APPLICATION

For use in recirculating paint systems. Ideal for flushing lines spray guns, and associated equipment. **RIDSOLVE 300W Gunwash** is diluted in DI water. To each 200 litres of **RIDSOLVE** add 800 litres of DI water.

4. TYPICAL DATA

| | |
|------------------|---------------------------|
| Appearance | Colourless to pale yellow |
| Odour | Alcohol / Glycol |
| Specific Gravity | 0.812 – 0.822 |
| Flash Point | 31°C |

5. STORAGE AND HANDLING

Highly flammable, stock should be held in closed drums in flammable goods store. Gloves and goggles should be worn when handling product.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.