



HENKEL Australia Pty Ltd
A.C.N. 001 302 996

135-141 Canterbury Road
KILSYTH VICTORIA 3164

Tel: (03) 9728 7200
Fax: (03) 9728 5877
Customer Service 1300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928
Mona Vale NSW 1660

Tel: (02)9979 6866
Fax: (02)9979 6864

Technical Data Bulletin

TURCO TURCOSOLV

Material No. 378340

SOLVENT CLEANER

DESCRIPTION:

TURCO TURCOSOLV is a clear, colourless solvent-based cleaner formulated to replace carbon tetrachloride and other hazardous solvents used for cleaning electrical equipment.

TURCO TURCOSOLV evaporates completely without leaving residues that can attract carbon dust, metallic particles or other contaminants that may damage electric equipment.

TURCO TURCOSOLV is also suitable for general maintenance cleaning of manufacturing, automotive, marine and transportation equipment.

TURCO TURCOSOLV removes greases, lube oils, rust preventative's, inks and hand marks from metallic as well as other surfaces. TURCO TURCOSOLV is not recommended for use on materials that are affected by chlorinated hydrocarbons.

BENEFITS:

TURCO TURCOSOLV offers these benefits:

1. Controlled evaporation. Leaves no residue.
2. Can be used on well-bonded paints.
3. Will not corrode metals.
4. Can be used on most electrical insulating materials.
5. Has dielectric strength of 40 k.v.a.

Note: No flash at initial boiling . This product may become flammable under certain use conditions.

USE INSTRUCTIONS:

SPRAY APPLICATIONS: Spray as received from pressure pot or non atomising spray with a 15 deg spray tip at a pressure of 15 to 30 psi. For in place spray cleaning of diesel electric generators, breathing apparatus must be worn during this application.

WIPE OR BRUSH APPLICATIONS: Use clean, lint-free cotton cloth or solvent resistant brushes.

DISPOSAL INFORMATION:

Dispose of spent solvent and/or rags per local, state and regional regulations. Refer to your local HENKEL Representative or the HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION:

TURCO TURCOSOLV contains chlorinated hydrocarbons and petroleum solvents. Use with adequate (equivalent to outdoor) ventilation. Do not spray in closed or confined areas. Avoid breathing of vapours for prolonged periods of time.

Avoid contact with eyes, skin and clothing. Do not take internally.

Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots, made from solvent-resistant neoprene should be worn when handling and using this product.

Containers exposed to moderate heat, above 32°C may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Do not use TURCO TURCOSOLV near welding arcs, torches and open flames, since hazardous gases may be formed. Rags used for application of TURCO TURCOSOLV may become combustible in time and should be stored in safety containers.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

JUNE 2002

® Registered Tradename HENKEL Australia Pty Ltd
® Disclaimer

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereon. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, HENKEL expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, express or implied is made concerning the goods described or the information provided herein nor shall HENKEL be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product

Email Address: admin@solvents.net.au