



Technologies

TECHNICAL BULLETIN

ABN: 82 001 302 996
135-141 Canterbury Road, Kilsyth Victoria 3137
Phone : (613) 9728 7200 Fax : (613) 9761 7179

TURCO[®] WHITE SOLV EC

NON FLAMMABLE SOLVENT CLEANER

1. DESCRIPTION:

TURCO WHITE SOLV EC is a clear colourless chlorinated hydrocarbon solvent cleaner with low viscosity and low surface tension.

TURCO WHITE SOLV EC is ideal for white room cleaning and cleaning of relay contacts, electrical equipment, assembled electronic units and precision components.

A few examples of the many cleaning applications for **TURCO WHITE SOLV EC** are:

- Aircraft-aerospace missile components.
- Electrical parts and assemblies.
- Hospital and research equipment.
- Instruments and precision parts.
- Precision bearings.
- Printed circuit boards.

2. BENEFITS:

TURCO WHITE SOLV EC offers these benefits:

1. Non flammable.
2. Fast evaporating.
3. High solvency for oils and grease.
4. Safe on paints, plastics and synthetic elastomers.
5. Easy to apply.
6. No mixing required.
7. Low toxicity.
8. Leaves no residue.

3. USE INSTRUCTIONS:

Apply to surface or metal by spray, brush or dip. For critical cleaning spray application is often preferred. Flush with **TURCO WHITE SOLV EC** until parts or surfaces are cleaned.

NOTE: When spraying use only a non-atomising nozzle.

4. DISPOSAL INFORMATION:

Dispose of rags and spent solvent per local, state and regional regulations. Refer to your local HENKEL REPRESENTATIVE or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

5. CAUTION:

TURCO WHITE SOLV EC contains chlorinated hydrocarbons. Use with adequate (equivalent to outdoor) ventilation. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid breathing of vapours for prolonged periods of time.

Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots made from solvent resistant neoprene should be worn when handling and using this product. Do not spray **TURCO WHITE SOLV EC** in closed or confined areas.

Do not use **TURCO WHITE SOLV EC** cleaner near welding arcs, torches and open flames, since hazardous gases may be formed. Containers exposed to moderate heat, above 32°C may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional handling, precautionary and first aid information.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.