

HENKEL Australia Pty Ltd A.C.N. 001 302 996

135-141 Canterbury Road KILSYTH VICTORIA 3164

Tel: (03) 9728 7200 Fax: (03) 9728 5877

Customer Service 1 300 736 777

Distributed by
Solvents Australia Pty Ltd
ABN 74 003 523 117
77 Bassett Street
Mona Vale NSW 2100
PO Box 928 Mona Vale NSW 1660

Tel: (02)9979 6866 Fax: (02)9979 6864

TECHNICAL DATA BULLETIN

WATER TREAT SA

Water Treat SA is Sulphuric Acid for effluent neutralisation

1. DESCRIPTION

Water Treat SA is sulphuric acid for effluent neutralisation

2. PROPERTIES

Total Acid (as H ₂ SO ₄)	% w/w	60
Iron (as Fe)	mg/kg	300 max
Heavy Metals (as Pb)	mg/kg	30 max
Density @ 15°C	kg/l	1.5 approximately

3. SAFETY PRECAUTIONS

Handle with extreme care, wear gloves, protective clothing and eye protection. In case of contact remove contaminated clothing and wash off with water. If in eyes, hold eyes open and flush with water for at least 15 minutes and see a doctor. For full information, refer to Material Safety Data Sheet.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

Ref. WTSA/AR/SJG Page 1 of 1

Issue Date: 14th August, 1998