



# Technologies

## TECHNICAL INFORMATION

### WATERTREAT HCL

Water Treat HCL is Hydrochloric Acid for Effluent Neutralisation

#### 1. INTRODUCTION

Water Treat HCL is Hydrochloric Acid for effluent neutralisation.

#### 2. PROPERTIES

Total Acidity (as HCl)	% w/w	32-34
Iron (as Fe)	mg/kg	35 max
Heavy Metals (as Pb)	mg/kg	10 max
Density @ 15°C	kg/l	12 approximately

#### 3. SAFETY PRECAUTIONS

Handle with extreme care, wear gloves, protective clothing and eye protection. In case of contact, remove contaminated clothing and wash off with water for at least 15 minutes and see a Doctor. For full information, refer to Material Safety Data Sheet.

#### DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

Henkel Australia Pty Limited  
ABN 82 001 302 996

P. O. Box 63  
Kilsyth Victoria 3137  
Australia

135-141 Canterbury Road  
Kilsyth Victoria 3137  
Australia

www.henkel.com  
Tel: (+61) 1300 736 777  
Fax: (+61) 3 9761 7179